

GOLD KOCHAV

PARTICULARS

Tonnage	Gross	Net
International(Primary)	59,835	25,783
Suez Canal	64,524	59,777
Panama Canal(PC/UMS)	59,917	26,323
Japanese Tonnage Certificate	N/A	

Dead Weight(Summer)	22,308 t	(scantling draught)
Light Weight	21,190 t	

Type, Class & Port of Registry etc	
Type	PCTC
Class	DNV
Class ID No	G114526
T/C Owner	N/A
Registered Owner	Bugle Shipping Co. Ltd.
Ship Managing Company	MSC Shipmanagement Limited
Manning Company	MSC Shipmanagement Limited
Port of Registry	Panama
Flag	Panama
Date of Keel Laid	2010-12-15
Date of Launching	2011-09-20
Date of Delivery	2012-04-11
IMO Number(Lloyds Code)	9463205
Official Number	43936-12-C
Call Sign	3FLQ2

E-Mail gold.kochav@mscfleet.com

Tel +357 250 308 07 Bridge
Tel +807 773 236 720 Bridge

Builder STX (Dalian) Shipbuilding Co., Ltd. (Hull no D-1006)

Principal Dimension	
L.O.A.	199.07 m
L.P.P.	190.50 m
Breadth(Mould)	32.27 m
Scantling draught (Mould)	11.20 m
Airdraft	48.2 m max keel to mast: 55.8 m

Machinery	
Main Engine(maker/type)	STX-MAN 7S60MC-C (MK-VIII)
Output (MCR)	16,660 kW
Output Post EEXI (MCR Limited)	10,740 kW

Diesel Generator(maker/type)	STX MAN B & W (7L21/31)
	1,540 kW each

Speed & Endurance			
Service Speed		19	Knots
F.O.Consumption(for M/E)	abt	61	MT/day
Endurance			Miles

Indicative consumption at Design Draft, BF<4 and DSS<3

Fuel Type	
Spec(FO)	380 cst
Spec(DO)	MDO

Tank Capacity	
W.B.T.	9,286.5 cbm (100%)
F.W.T.	250.0 cbm (100%)
F.O.T.	2,720.5 cbm (100%)
D.O.T.	697.6 cbm (100%)

Side Thruster	
Bow Thruster	1,500 kW
Stern Thruster	not fitted kW

Car Handling Equipments	
Stern Quarter Ramp	
Position	Starboard Quarter
Size	45 m x 7 m driveway width
Opening Size	4.40 m x 15.0 m
Load Base	125 SWL tons

Side Ramp	
Position	Starboard
Size	25 m x 4.5 m driveway width
Opening Size	4.40 m x 4.50 m
Load Base	30 SWL tons

Cargo Capacity					
Deck	Clear height (mm)	Type of deck	SQM	Axle load (t)	Uniform load (tons/m ²)
13	1850	Fixed	3,367	1.2/2	0.18
12	1850	Fixed	5,756	1.2/2	0.18
11	1850	Fixed	5,780	1.2/2	0.18
10	2000	Fixed	5,805	1.5/2	0.20
9	2000	Fixed	5,819	1.5/2	0.20
8	2000/1700	Liftable	5,757	1.5/2	0.22
7	2000/2300/4000	Fixed	5,050	8.0/2	0.70
6	2200/1700	Liftable	5,098	2.0/2	0.25
5	2200/2700/4400	Fixed	4,805	25/2 # 15/2	2.00
4	2200/1700	Liftable	3,373	2.0/2	0.25
3	2400/2900/4400	Fixed	3,079	10.0/2	1.50
2	2000/1700	Liftable	1,749	1.5/2	0.22
1	2000/2300/4000	Fixed	1,409	10.0/2	1.50
Total m ²			56,845		

25/2 (AFT) 15/2(FWD)