

# Viking Bravery

# PARTICULARS

Tonnage	Gross	Net
International(Primary)	62,106	20,053
Suez Canal	65,413	61,319
Panama Canal(PC/UMS)		62,111
Japanese Tonnage	39,878	
Dead Weight(Summer)	18,446	(scantling draught)
Light Weight	17,825	

Type, Class & Port of Registry etc		
Type	PCTC	
Class	DNV	
Class ID No		
T/C Owner	Gram Car Carriers Leasing 1 AS	
Registered Owner	Fortune Truck Shipping Ltd.	
Ship Managing Company	OSM Ship Management Pte. Ltd	
Manning Company	OSM Ship Management Pte. Ltd	
Port of Registry	Majuro	
Flag	Marshall Islands	
Date of Keel Laid	06 May 2014	
Date of Launching	22 October 2014	
Date of Delivery	30 April 2015	
IMO Number(Lloyds Code)	9673020	
Official Number	9727	
Call Sign	V7A5090	

Sat-C Telex	456580610	
Sat-C E-mail	<a href="mailto:456580610@inmc.eik.com">456580610@inmc.eik.com</a>	Text e-mail only
E-Mail	<a href="mailto:master@viking-bravery.osm.no">master@viking-bravery.osm.no</a>	Master
E-Mail	<a href="mailto:bridge@viking-bravery.osm.no">bridge@viking-bravery.osm.no</a>	Bridge
MMSI	538009727	
VSAT Tel	+ 44 1322 788 282	Master
VSAT Tel	+ 65 3163 2709	Bridge
FBB Tel	+ 870 773 935 187	Bridge

Builder	CSC JINLING SHIPYARD (Hull JLZ8120413)
---------	--

Principal Dimension	
L.O.A.	199.900 m
L.P.P.	190.000 m
Breadth(Mould)	32.260 m
Scantling draught (Mould)	10.000 m

Machinery		
Main Engine(maker/type)	MAN B&W 6S60 ME-C8.2 Tier II	
Output	12,200 kw	
Diesel Generator(maker/type)	3 x 6L21/31 - MAN Diesel & Turbo SE (Zhenjiang)	
	1,320 kw each	

Speed & Endurance			
Service Speed(C/P)	16	Knots	Indicative consumption at Design Draft, BF<4 and DSS<3
F.O.Consumption(for M/E)	30	MT/day	
Endurance	20,000	Miles	

Fuel Type		
Spec(FO)	380	cst
Spec(DO)	MDO	

Tank Capacity		
W.B.T.	6,400.0	cbm
F.W.T.	300.0	cbm
F.O.T.	3,000.0	cbm
D.O.T.	300.0	cbm

Side Thruster		
Bow Thruster	1,800	kw
Stern Thruster	not fitted	kw

Car Handling Equipments		
Stern Quarter Ramp		
Position	Starboard Quarter	
Size	31,5 x 7.5m driveway width	
Opening Size	12 m (B) x 5.4m/3.34/2.80 (H)	
Load Base	150	tons

Side Ramp		
Position	Starboard	
Size	21.5 x 4.5 driveway width	
Opening Size	5,4 (B) x 5.88/2.8/3.34	
Load Base	22	tons

Cargo Capacity						
Deck	Clear height (mm)	Type of deck	SQM	Axle load (t)	Uniform load (tons/m²)	
12	2000	Fixed	5572	1,6/2	0.25	
11	2000	Fixed	5716	1,6/2	0.3	
10	2000	Fixed	5716	1,6/2	0.25	
9	2200	Fixed	5716	1,6/2	0.3	
8	1700/2100	Liftable	5716	1,6/2	0.3	
7	2200/2600/4300	Fixed	4998	15/2	0.75	
6	1900/2400	Liftable	5294	1,6/2	0.3	
5	2800/3340/5200	Fixed	5133	25/2 & 55/4	2.5	
4	2400	Liftable	3645	16.2	0.3	
3	2200/4600	Fixed	3551	15/2 & 25/4	2	
2	1700	Liftable	3046	1,6/2	0.3	
1	2000/3700	Fixed	2691	15/2	1	
Total m²			56,794			